

## **Additional information to manual Dehumidifier D812**

### **WIFI SETUP**

1. Make sure the device is plugged into a power outlet and placed near a Wi-Fi router.
2. Make sure the phone's bluetooth is enabled. In addition, it is important that the Wi-Fi network the device will be connected to is a 2.4 GHZ network.
3. First, download the "SMART LIFE" app on a mobile phone and then open it.
4. It is important to follow the steps in the app that indicate how the device gets connected.
5. Turn on the dehumidifier using the ON/OFF button.
6. Press and then hold down the "TIMER" button for at least 3 seconds. At that time, the "WATER TANK FULL" LED will start flashing at a fast rate with a red colour.
7. If all goes well, the device now becomes visible in the app for pairing. This can be done with the model number (this starts with YL-XXXX, or with the PVG model name D812)
8. Click on the device in the app to connect. The app and device will now go through the verification process. This may take several minutes.






Note #1: If the LED does not start flashing when the "TIMER" button has been pressed for 3 seconds, the unit must be reconnected. To do this, follow the steps from 1 to 6 again.

Note #2: If the device does not show up in the app for subsequent pairing, but the red LED does flash, the wifi network is most likely not a 2.4 GHz network or the bluetooth is not enabled on the phone. Next, check this to find out what the cause could possibly be.



## CONTROL PANEL



### FUNCTIONS AND NAME OF KEY PADS

1. Press and hold this button to switch the device on or off (ON/OFF).   
*When the device is switched on, the indicator will light up (POWER LIGHT)*
2. Press and hold this button to set the desired humidity, this can be changed to 40%, 50% or 60% (HUMIDITY).   
*When the desired set humidity has been achieved, the green light will come on and the dehumidifier will continue to operate according to the set humidity (40%, 50%, 60% HUMIDITY INDICATOR).*  
*When the dehumidifier is in "CONT" mode, the light on the display will illuminate (CONT INDICATOR).*
3. When the unit is switched on, press the "TIMER" to set a time, this can vary between 2, 4 and 6 hours (TIMER). 
4. This light will illuminate when the unit's water tank is full (WATER FULL).   
*When the water tank is full, the indicator light turns on and the dehumidifier immediately stops working (WATER FULL INDICATOR).*
5. When this light is on, the appliance is in defrost mode (DEFROST).   
*When the machine is operating in "DEFROST" mode, the light of this function turns on.*

### OPERATION OF KEY PADS

1. When the dehumidifier is plugged into the socket, the device first goes into "STANDBY"  
*ON: Press on the button, the dehumidifier will start working.*  
*OFF: Press on the button, the dehumidifier will stop working.* 
2. The humidity can be adjusted with this humidifier (HUMIDITY SET).  
*With the "CONT" function it shows the humidity in the circulation of the tube of the device. This can range from 40%, 50% to 60%.* 
3. When the dehumidifier is turned on, you can press the button on the "TIMER" function to set a time that the device will operate. The time can vary from 2h, 4h, or 6h. Press the desired time to set the time. The timer light will then light up and the selected time will be shown on the display.